

## NRT-T2

## Multi-Biometric

## Time Attendance

Network Series









- 4 in 1 Verification Method
- Breakthrough Geographical Boundaries
- Achieve Management Centralization
- Lightning Fast Recognition Speed
- Simplest User-Interface Design



## Specification

Display Language

NRT-T2	Face Capacity	500
Black	Fingerprint Capacity	3,000
2.8" TFT LCD	Card Capacity	3,000
Face / Fingerprint / Card / PIN	Log Capacity	200,000
≤lsec	Working Voltage	DC 5V
EM / MiFare Card	Working Temperature	0°C - 60°C
158 x 154 x 32.5mm	Working Humidity	20% - 80%
TCP/IP, USB Drive, [Optional WiFi]		
	Black 2.8" TFT LCD Face / Fingerprint / Card / PIN ≤ 1 sec EM / MiFare Card 158 x 154 x 32.5mm	Black Fingerprint Capacity  2.8" TFT LCD Card Capacity  Face / Fingerprint / Card / PIN Log Capacity  ≤1 sec Working Voltage  EM / MiFare Card Working Temperature  158 x 154 x 32.5mm Working Humidity

English, Chinese, Thai, Viet, Spanish, and more

<sup>\*</sup> The specifications are subjected to change without notice.



Unit 3, 2/F., Block A, Hong Kong Industrial Centre, 489-491 Castle Peak Road, Kowloon, Hong Kong Tel: +(852) 2745 1342 Fax: +(852) 2786 4647 E-mail: info@union-business.com Website: https://www.union-business.com

